

## FUEL INJECTION VALVE

**Patent number:** WO02059477

**Publication date:** 2002-08-01

**Inventor:** HOHL GUENTHER (DE); KEIM NORBERT (DE)

**Applicant:** BOSCH GMBH ROBERT (DE); HOHL GUENTHER (DE); KEIM NORBERT (DE)

**Classification:**

- **International:** F02M61/06; F02M61/18; F02M51/06

- **European:** F02M51/00C; F02M51/06B2E2; F02M61/06; F02M61/12; F02M61/16B; F02M61/16C; F02M61/16D; F02M61/18

**Application number:** WO2002DE00242 20020124

**Priority number(s):** DE20011003051 20010124

**Also published as:**

WO02059477 (A3)  
EP1356202 (A3)  
EP1356202 (A2)  
US6866210 (B2)  
US2004021010 (A1)

[more >>](#)


**Cited documents:**

GB2185070  
DE932209  
US4523719  
DE3710467

[Report a data error here](#)

**Abstract of WO02059477**

The invention relates to a fuel injection valve for fuel injection systems of internal combustion engines, comprising a valve closing body (4) that is functionally linked with a valve needle (3) and that interacts with a valve face (6) arranged in a recess of a valve seat body (5) to give a sealing seat, and at least one injection opening (7) arranged in the valve seat body (5). The recess of the valve seat body (5) defines a second surface (36) between the valve face (6) and the injection opening (7) which surface includes a more acute angle (  $\beta$  ) with the median axis (37) of the fuel injection valve (1) than the valve face (6). A closing body projection (35) disposed on the down-stream end of the valve closing body (4) has a peripheral surface (39) that forms an obtuse angle with the adjoining contour of the valve closing body (4).



Data supplied from the **esp@cenet** database - Worldwide